

fsavschedule

<support@F-Secure.com>

Juha Autero2003-02-27

Name

fsavschedule — database update and file scan scheduler for F-Secure Anti-Virus for Linux

Synopsis

fsavschedule

DESCRIPTION

fsavschedule is a shell script for scheduling the Virus Definition Database update and file scan cron(8) jobs for F-Secure Anti-Virus for Linux. Run **fsavschedule** to answer to some questions and to add lines to user's crontab(5).

Since cron(8) will mail output of job to user, local mail delivery should be configured when using scheduled jobs. **dbupdate** will also write `dbupdate.log` in database directory.

Note

Default installation of Red Hat 7.1 or later does not have working local mail delivery. See Knowledge Base Article Sendmail does not work after installation (<http://kb.redhat.com/view.php?eid=314>).

EXAMPLES

Here is an example of running **fsavschedule**.

Example 1. Running fsavschedule

```
$/opt/f-secure/fsav/bin/fsavschedule
F-Secure Anti-Virus automatic scan and update scheduler
Copyright (c) 1999-2004 F-Secure Corporation. All Rights Reserved.
```

This program will schedule automatic virus scans and updates of the F-Secure Anti-Virus virus database using the cron facility. We will now ask you some questions about running these processes. A default value will be shown in square brackets after the question. To accept the default, just press return.

Would you like to schedule an automatic database update run [yes]? yes

How often would you like updates to be performed (hourly/daily) [hourly]? hourly
Would you like to schedule an automatic virus scan [no]? yes
Which directories would you like to scan? [/]? /home
How often would you like the scans to be performed (hourly/daily/weekly) [daily]? daily
At what hour should the scan be run (0-23) [6]? 4
At what minute should the scan be run (0-59) [0]? 12

Successfully scheduled a scanning run.
Successfully scheduled an update run.

If for some reason you wish to disable automatic runs, run the command
`crontab -e`. This will bring up your current crontab in an editor.
Then remove the following line from the file and save it:

```
12 4 * * * /opt/f-secure/fsav/bin/fsav /home  
8 * * * * /opt/f-secure/fsav/bin/dbupdate
```

Bugs

Please refer to 'Known Problems' -section in release notes.

AUTHORS

F-Secure Corporation

Copyright

Copyright (c) 1999-2004 F-Secure Corporation. All Rights Reserved.

SEE ALSO

`fsav(1)`, `dbupdate(8)` and `cron(8)`

For more information, see F-Secure home page (<http://www.F-Secure.com/anti-virus/webclub/>).